

TDD-TM1560CB

Touch Monitors



Overview

With slim design, wide-angle viewing and vivid colors, TDD touch monitors is an incredibly powerful touch solution based on the latest 4 Wire or 5 Wire Resistive, SAW (surface acoustic wave), infrared or capacitive touch technology. Featuring with high resolution, wide viewing angle, VESA mounting, flexible connectivity and lightweight, TDD touch monitors allow users to enjoy richer & better quality image, easy viewing and seamless connections.

Features

- Slim & compact space-saving design black case with V base, tempered glass & resistive or capacitive USB touch
- Wide-angle viewing & vivid colors performance
- Mercury (HG) free LED panel
- Stand with adjustable viewing angle
- Internal or external power supply unit option
- VESA mount compliance
- Low Power Consumption

Specifications

Screen Size	15.6" LED (16:9), 39.5cm
Maximum Resolution	1366 x 768 (1.0 megapixel)
Pixel Pitch	0.252 (H)×0.52 (V)mm
Display Area	344.232 (H)×193.536 (V)mm
Brightness	200 cd/m ²
Contrast Ratio	500:1
Response Time	3/5 (Typ.)(Tr/Td) ms
Viewing Angle	45/45/20/45 (Typ.)(CR≥10)
Scan Frequency	60Hz
Display Colours	16.7M , 65% (CIE1931)
Input Signal	VGA x1, USB x1 for touch
VESA Mounting	100 x 100mm
Power Supply	AC 100 - 240V, 50/60Hz
Power Consumption	Power on: <30W (max), standby: <1W
Accessories	Power supply, power cable, USB cable, VGA cable, manual

Remark: Available sizes for same case: 15.6", 18.5", 19.5", 19.53"

* TDD (www.tddgrouppltd.com, sales@tddgrouppltd.com) reserves the right to change specifications without prior notice.